

Combimaster DX

The inexpensive alternative for universal use as a push-up ladder and stepladder.

Product description

- Can be used as a 2-part push-up ladder or as a ladder with double-sided access.
- Strong Perlon straps.
- With cross-tube for stability.
- Robust extruded-section triangular rungs with step horizontal in working position.
- High strength, non-twist rung/stile connections.
- Stiles and guide fittings of extruded aluminium sections for maximum safety.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Base: 1,64 m × 0,89 m
 Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged multi-function ladder, 2-section
 Tread depth: 38 mm
 Type rung/tread: serrated

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Length as trestle	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
44868	2.25 m	8	2 × 8	3.82 m	2.4 m	58 mm	2.400 mm × 420 mm × 120 mm	10 kg	0.89 m	4.9 m
44870	2.81 m	10	2 × 10	4.94 m	2.98 m	68 mm	2.970 mm × 430 mm × 120 mm	12.3 kg	0.9 m	5.7 m
44872	3.33 m	12	2 × 12	6.06 m	3.54 m	73 mm	3.530 mm × 430 mm × 130 mm	15.3 kg	1 m	6.8 m
44874	3.86 m	14	2 × 14	6.9 m	4.1 m	85 mm	4.090 mm × 430 mm × 135 mm	18.2 kg	1.1 m	7.6 m