

# Combimaster X

Practical dual-function ladder that can be used as a single ladder or stepladder for flexible application.

## Product description

- Can be used as either a single ladder or a stepladder.
- Strong, steel joint bolted to the stiles.
- Self-locking.
- One ladder section with broad horizontal stabiliser bar.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



## Product features

Coating: natural  
 Connection Stile-Rung: flanged  
 Load: max. 150 kg  
 Material: Aluminium  
 Pitch rung/tread: 265 mm  
 Producttype: Flanged multi-function folding ladder, 2-section  
 Stile depth: 58 mm  
 Tread depth: 30 mm  
 Type rung/tread: serrated

## Hints and special features

Complies with EN 131 Professional.

## Product variants

Order number	Length as lean-to ladder	Length as stepladder	Number of rungs	Number of rungs	Transport dimensions	Weight	Wide crosspiece	Working height as lean-to ladder	Working height as stepladder
41941	2.5 m	1.3 m	4	2 × 4	1.265 mm × 360 mm × 130 mm	6 kg	0.75 m	3.35 m	2.55 m
41942	3.6 m	1.85 m	6	2 × 6	1.870 mm × 360 mm × 130 mm	8 kg	0.8 m	4.4 m	3.1 m
41943	4.7 m	2.4 m	8	2 × 8	2.410 mm × 360 mm × 130 mm	12 kg	0.9 m	5.45 m	3.6 m