

Everest 2E

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 External width of lower ladder: 490 mm
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 270 mm
 Producttype: Flanged push-up ladder with rungs, 2-section
 Tread depth: 30 mm
 Type rung/tread: serrated
 Wheels: Rubber

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
40245	6	2 × 6	2.95 m	1.83 m	58 mm	1.830 mm × 500 mm × 130 mm	6 kg		3.8 m
40246	8	2 × 8	4.07 m	2.39 m	58 mm	2.390 mm × 500 mm × 130 mm	9.8 kg	0.9 m	4.85 m
40247	10	2 × 10	4.96 m	3 m	68 mm	3.000 mm × 500 mm × 140 mm	13.5 kg	1 m	5.75 m
40248	12	2 × 12	6.09 m	3.56 m	73 mm	3.570 mm × 500 mm × 160 mm	18 kg	1.1 m	6.8 m



Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
40249	14	2 × 14	7.21 m	4.07 m	73 mm	4.130 mm × 500 mm × 160 mm	19.5 kg	1.2 m	7.9 m
40214	16	2 × 16	8.33 m	4.7 m	98 mm	4.690 mm × 500 mm × 180 mm	25 kg	1.2 m	9 m
40215	18	2 × 18	9.13 m	5.2 m	98 mm	5.210 mm × 500 mm × 230 mm	27.5 kg	1.2 m	9.75 m
40216	20	2 × 20	10.25 m	5.74 m	114 mm	5.770 mm × 500 mm × 230 mm	33 kg	1.2 m	10.85 m
40217	24	2 × 24	12.22 m	6.9 m	114 mm	6.900 mm × 500 mm × 230 mm	41.54 kg	1.2 m	12.75 m