

# Mobile access steps with platform, double-sided access, with light-alloy treads and platform

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.

## Product description

- Quick and easy assembly thanks to the new connecting elements.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Maximum loading capacity 150 kg.



## Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.  
Complies with EN 131-7

## Product features

Coating: natural  
 Connection Stile-Rung: welded  
 Guardrail height: 1000 mm  
 Load: max. 150 kg  
 Material: Aluminium  
 Pitch rung/tread: 240 mm  
 Platform length: 800 mm  
 Platform width: 600 mm  
 Tread depth: 200 mm  
 Type rung/tread: serrated

## Product variants

Order number	Base	Number of rungs, incl. platform	Number of treads	Platform height	Transport dimensions	Weight	Working height
41981	0,77 m × 1,51 m	2 × 3	3	0.72 m	1.300 mm × 820 mm × 470 mm	31.2 kg	2.7 m
41982	0,82 m × 1,79 m	2 × 4	4	0.96 m	1.980 mm × 880 mm × 300 mm	36 kg	2.95 m
41983	0,87 m × 2,06	2 × 5	5	1.2 m	1.850 mm × 940 mm × 440 mm	41 kg	3.2 m



Order number	Base	Number of rungs, incl. platform	Number of treads	Platform height	Transport dimensions	Weight	Working height
	m						
41984	0,93 m × 2,34 m	2 × 6	6	1.44 m	2.200 mm × 1.020 mm × 410 mm	46.2 kg	3.45 m
41985	0,98 m × 2,62 m	2 × 7	7	1.68 m	2.250 mm × 1.060 mm × 410 mm	51.7 kg	3.7 m
41986	1,03 m × 2,9 m	2 × 8	8	1.92 m	2.820 mm × 1.120 mm × 410 mm	57.5 kg	3.9 m