




Mobile access steps with platform

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Cantilever platform available for bridging obstacles.
- Chassis available in a non-static version as an option.
- Narrow chassis. The chassis width is reduced to a minimum through additional ballasting.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

Product variants

Order number	Chassis width	Inclination	Number of treads	Overall span	Tread width	Vertical height
40255764	1020 mm	45 °	5	1698 mm	600 mm	1070 mm
40255766	1620 mm	45 °	7	2128 mm	600 mm	1500 mm
40255768	1620 mm	45 °	9	2558 mm	600 mm	1930 mm
40255770	1220 mm	45 °	11	3017 mm	600 mm	2360 mm
40255772	1220 mm	45 °	12	3447 mm	600 mm	2790 mm
40255774	1220 mm	45 °	14	3877 mm	600 mm	3220 mm
40255776	1220 mm	45 °	16	4307 mm	600 mm	3650 mm
40255778	1420 mm	45 °	18	4737 mm	600 mm	4080 mm
40255780	1420 mm	45 °	20	5167 mm	600 mm	4510 mm

Order number	Chassis width	Inclination	Number of treads	Overall span	Tread width	Vertical height
40255784	1020 mm	45 °	5	1698 mm	800 mm	1070 mm
40255786	1220 mm	45 °	7	2128 mm	800 mm	1500 mm
40255788	1220 mm	45 °	9	2558 mm	800 mm	1930 mm
40255790	1220 mm	45 °	11	3017 mm	800 mm	2360 mm
40255792	1220 mm	45 °	12	3447 mm	800 mm	2790 mm
40255794	1420 mm	45 °	14	3877 mm	800 mm	3220 mm
40255796	1420 mm	45 °	16	4307 mm	800 mm	3650 mm
40255798	1420 mm	45 °	18	4737 mm	800 mm	4080 mm
40255800	1620 mm	45 °	20	5167 mm	800 mm	4510 mm
40255804	1420 mm	45 °	5	1698 mm	1000 mm	1070 mm
40255806	1420 mm	45 °	7	2128 mm	1000 mm	1500 mm
40255808	1420 mm	45 °	9	2558 mm	1000 mm	1930 mm
40255810	1420 mm	45 °	11	3017 mm	1000 mm	2360 mm
40255812	1420 mm	45 °	12	3447 mm	1000 mm	2790 mm
40255814	1420 mm	45 °	14	3877 mm	1000 mm	3220 mm
40255816	1420 mm	45 °	16	4307 mm	1000 mm	3650 mm
40255818	1420 mm	45 °	18	4737 mm	1000 mm	4080 mm
40255820	1620 mm	45 °	20	5167 mm	1000 mm	4510 mm
40255704	1220 mm	60 °	5	1453 mm	600 mm	1250 mm
40255706	1420 mm	60 °	7	1707 mm	600 mm	1750 mm
40255708	1820 mm	60 °	9	1996 mm	600 mm	2250 mm
40255710	1620 mm	60 °	11	2285 mm	600 mm	2750 mm
40255712	1620 mm	60 °	12	2607 mm	600 mm	3250 mm
40255714	1620 mm	60 °	14	2896 mm	600 mm	3750 mm
40255716	1620 mm	60 °	17	3185 mm	600 mm	4250 mm
40255718	2020 mm	60 °	19	3496 mm	600 mm	4750 mm
40255720	2020 mm	60 °	21	3785 mm	600 mm	5250 mm
40255724	1220 mm	60 °	5	1453 mm	800 mm	1250 mm
40255726	1220 mm	60 °	7	1707 mm	800 mm	1750 mm
40255728	1620 mm	60 °	9	1996 mm	800 mm	2250 mm
40255730	1420 mm	60 °	11	2285 mm	800 mm	2750 mm
40255732	1420 mm	60 °	12	2607 mm	800 mm	3250 mm
40255734	1420 mm	60 °	14	2896 mm	800 mm	3750 mm
40255736	1620 mm	60 °	17	3185 mm	800 mm	4250 mm
40255738	2020 mm	60 °	19	3496 mm	800 mm	4750 mm
40255740	2020 mm	60 °	21	3785 mm	800 mm	5250 mm
40255744	1420 mm	60 °	5	1453 mm	1000 mm	1250 mm

Order number	Chassis width	Inclination	Number of treads	Overall span	Tread width	Vertical height
40255746	1420 mm	60 °	7	1707 mm	1000 mm	1750 mm
40255748	1420 mm	60 °	9	1996 mm	1000 mm	2250 mm
40255750	1420 mm	60 °	11	2285 mm	1000 mm	2750 mm
40255752	1420 mm	60 °	12	2607 mm	1000 mm	3250 mm
40255754	1420 mm	60 °	14	2720 mm	1000 mm	3750 mm
40255756	1620 mm	60 °	17	3207 mm	1000 mm	4250 mm
40255758	1820 mm	60 °	19	3496 mm	1000 mm	4750 mm
40255760	2020 mm	60 °	21	3785 mm	1000 mm	5250 mm