

Skymaster DX

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

Product description

- Robust extruded-section triangular rungs with step horizontal in working position.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Producttype: Flanged multi-function ladder, 3-section
 Tread depth: 38 mm
 Type rung/tread: serrated

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height as 3-part single ladder
44837	4.4 m	3.25 m	7	3 × 7	2.14 m	58 mm	2.130 mm × 500 mm × 170 mm	13.8 kg	0.8 m	5.2 m
44838	5.25 m	3.85 m	8	3 × 8	2.42 m	68 mm	2.410 mm × 500 mm × 170 mm	16.3 kg	0.9 m	6 m
44839	6.1 m	4.4 m	9	3 × 9	2.7 m	73 mm	2.690 mm × 500 mm × 190 mm	18 kg	1 m	6.85 m
44840	6.65 m	4.65 m	10	3 × 10	2.98 m	73 mm	2.970 mm × 500 mm × 190 mm	20.5 kg	1.1 m	7.35 m
44841	7.2 m	5.25 m	11	3 × 11	3.26 m	85 mm	3.270 mm × 500 mm × 200 mm	22.3 kg	1.1 m	7.9 m
44842	8.3 m	5.8 m	12	3 × 12	3.54 m	85 mm	3.550 mm × 500 mm × 220 mm	25.9 kg	1.2 m	9 m



Order number	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-on section	Number of rungs	Number of rungs	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height as 3-part single ladder
44844	9.45 m	6.654 m	14	3 × 14	4.1 m	98 mm	4.110 mm × 500 mm × 220 mm	31.5 kg	1.2 m	10.05 m