

CompactMaster S-PLUS 2T

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

Product description

- Scaffolding width: 0.85 m or 1.45 m (lower section incl. hinges); Scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 150 mm swivel castors (order no. 42759) for millimetre-perfect level adjustment.



Product features

Claw type: automatic
 Fits through doorways: No
 Platform length: 1.8 m
 Platform length: 1.8 m
 Platform size: 1,2m × 1,8m
 Platform width: 1.2 m
 Rung diameter: 50 mm
 Scaffolding class: 3 (= 200 kg/m²)
 Stile diameter: 50 mm
 Width scaffolding: 1.45 m

Product variants

Order number	Height-adjustable castors:	Overall height	Platform height	Transport dimensions	Weight	Wheel diameter	Working height
53400	No	1.65 m	0.95 m	0 mm × 0 mm × 0 mm	52.8 kg	125 mm	2.95 m
53199	Yes	3 m	1.75 m	0 mm0 mm0 mm	108.1 kg	150 mm	3.75 m
53221	Yes	3.85 m	2.6 m	0 mm0 mm0 mm	161.4 kg	150 mm	4.6 m
53231	Yes	4.95 m	3.7 m	0 mm0 mm0 mm	189.4 kg	150 mm	5.7 m
53241	Yes	5.8 m	4.55 m	0 mm0 mm0 mm	225 kg	150 mm	6.55 m

Order number	Height-adjustable castors:	Overall height	Platform height	Transport dimensions	Weight	Wheel diameter	Working height
53251	Yes	6.9 m	5.65 m	0 mm0 mm0 mm	250.7 kg	150 mm	7.65 m
53261	Yes	7.75 m	6.5 m	0 mm0 mm0 mm	284 kg	150 mm	8.5 m
53271	Yes	8.9 m	7.6 m	0 mm0 mm0 mm	312 kg	150 mm	9.6 m
53281	Yes	9.7 m	8.4 m	0 mm0 mm0 mm	345.3 kg	150 mm	10.45 m
53291	Yes	10.85 m	9.6 m	0 mm0 mm0 mm	373.3 kg	150 mm	11.6 m
53201	Yes	11.7 m	10.4 m	0 mm0 mm0 mm	406.6 kg	150 mm	12.4 m
53211	Yes	12.8 m	11.55 m	0 mm0 mm0 mm	434.6 kg	150 mm	13.55 m